

## CÁNCAMOS DE ELEVACIÓN UNIVERSAL - DSS



DSS																	
Referencia	CMU	Coef. seguridad	Diámetro	ø	P	Standard L1	N.m	FootLBS	S	A	B	C	D	E	F	G	Peso
DSS M 24	4,5 TO	5	M24 (x3)			36	160	19		61	31	70	104	73	145	29	5,4 Kg
DSS M 30	7,3 TO	5	M30 (x3,5)			45	250	19		61	31	70	104	73	145	29	5,5 Kg
DSS M 33	8 TO	5	M33 (x3,5)			50	250	19		61	31	70	104	73	145	29	5,5 Kg
DSS M 36	10 TO	5	M36 (x4)			54	320	19		61	31	70	104	73	145	29	5,5 Kg
DSS M 36x3	10 TO	5	M36 (x3)			54	320	19		61	31	70	104	73	145	29	5,5 Kg
DSS M 39	10 TO	5	M39 (x4)			58	320	19		61	31	70	104	73	145	29	5,7 Kg
DSS M 42	12,5 TO	5	M42 (x4,5)			63	400	19		61	31	70	104	73	145	29	5,8 Kg
DSS M 42x3	12,5 TO	5	M42 (x3)			63	400	19		61	31	70	104	73	145	29	5,8 Kg
DSS M 45	15 TO	4	M45 (x4,5)			63	400	19		61	31	70	104	73	145	29	5,9 Kg
DSS M 48	20 TO	4	M48 (x5)			68	600	19		79	38	90	125	91	184	36	11 Kg
DSS M 48x3	20 TO	4	M48 (x3)			68	600	19		79	38	90	125	91	184	36	11 Kg
DSS M 48x4	20 TO	4	M48 (x4)			68	600	19		79	38	90	125	91	184	36	11 Kg
DSS M 52	20 TO	4	M52 (x5)			68	600	19		79	38	90	125	91	184	36	11,2 Kg
DSS M 56	25 TO	4	M56 (x5,5)			78	600	19		79	38	90	125	91	184	36	11,3 Kg
DSS M 56x4	25 TO	4	M56 (x4)			78	600	19		79	38	90	125	91	184	36	11,4 Kg
DSS M 64	32,1 TO	4	M64 (x6)			90	600	19		79	38	95	125	91	184	36	12,2 Kg
DSS M 64x4	32,1 TO	4	M64 (x4)			90	600	19		79	38	95	125	91	184	36	12,2 Kg
DSS M 72	25 TO	4	M72 (x6)			90	600	19		79	38	95	125	91	184	36	14 Kg
DSS M 72x4	25 TO	4	M72 (x4)			90	600	19		79	38	95	125	91	184	36	14 Kg
DSS M 80	32,1 TO	4	M80 (x6)			90	600	19		79	38	95	125	91	184	36	15 Kg
DSS M 90	32,1 TO	4	M90 (x6)			90	600	19		79	38	95	125	91	184	36	15,5 Kg
DSS M 100	32,1 TO	4	M100 (x6)			90	600	19		79	38	95	125	91	184	36	16,5 Kg
DSS U 100	10,000 LBS	5	UNC 1"-8			36	160	19		61	31	70	104	73	145	29	5,4 Kg
DSS U 125	14,000 LBS	5	UNC 1"1/4-7			45	200 F.L	3/4"		61	31	70	104	73	145	29	5,4 Kg
DSS U 138	20,000 LBS	5	UNC 1"3/8-6			54	300 F.L	3/4"		61	31	70	104	73	145	29	5,4 Kg
DSS U 150	20,000 LBS	5	UNC 1"1/2-6			54	300 F.L	3/4"		61	31	70	104	73	145	29	5,4 Kg
DSS U 200	50,000 LBS	4	UNC 2"-4 1/2			76	450 F.L	3/4"		79	38	90	125	91	184	33	11,1 Kg
DSS U 250	55,000 LBS	4	UNC 2"1/2-4			90	600	19		79	38	95	125	91	184	36	12,2 Kg